

### Installed in minutes - saves energy and costs

#### Step 1:

Apply the self-adhesive Velcro tape to the inside of your door frame.

#### Step 2:

Attach the door seal to the Velcro tape.

#### Step 3:

Unzip and attach your air conditioning hose to the door seal.

#### Step 4:

Close the zip tightly around the hose. You can use cable ties (not included) for better fixation.

#### Application:

This Hot Air Stop is suitable for all sliding doors up to a size of 87x208 cm.

### Scope of delivery

- Hot Air Stop
- Velcro tape
- Instructions for use

### Warranty period


- 2 years

### The energy-saving installation solution for air conditioners!

The door seal is attached using the Velcro tape supplied.

The door seal can be removed at any time without leaving any residue.

- Suitable for doors with a maximum circumference of 87x208 cm.
- The door seal for air conditioners is a practical helper and can be attached to the balcony door in just a few steps. Simply stick the supplied adhesive tape into the door frame, attach the door seal to the door frame and you're done.
- Sealing the door increases the cooling capacity of the local air conditioner. This reduces the overall energy consumption as the room can be cooled faster.
- The zip system allows you to continue to use the door comfortably even when the air conditioning is on, but at the same time provides perfect protection from insects (like a fly screen) and also prevents moisture from entering.
- Due to the two zip openings, the door seal is suitable for all portable air conditioners regardless of the manufacturer.
- Easy installation without drilling and without additional tools.
- The material is durable, UV-resistant, water-repellent and washable at 40°C.



Example 1



Example 2



Example 3