

Installed in minutes - saves energy and costs**Step 1:**

Apply the self-adhesive Velcro tape to the inside of your door frame.

Step 2:

Attach the door seal to the Velcro tape.

Step 3:

Unzip and attach your air conditioning hose to the door seal.

Step 4:

Close the zip tightly around the hose.

Application:

This Hot Air Stop is suitable for all sliding doors up to 87x208 cm.

Scope of delivery

- Hot Air Stop
- Velcro tape
- Instructions for use

Warranty period

- 2 years

The energy-saving installation solution for air conditioners!

The door seal for balcony and patio doors is attached using the Velcro tape supplied. The door seal can be removed at any time without leaving any residue.

- Suitable for balcony and veranda doors with a maximum circumference of 560cm.
- The door seal for air conditioners is a practical helper and can be attached to the balcony door in just a few steps. Simply stick the supplied adhesive tape into the door frame, attach the door seal to the door frame and you're done.
- Sealing the door increases the cooling capacity of the air conditioner. This reduces the overall energy consumption as the room is cooled faster.
- The zip system allows you to continue using the door comfortably even when the air conditioner is on, but at the same time provides perfect protection against insects (like a fly screen) and also prevents moisture from entering.
- Due to the two zip openings, the door seal is suitable for all portable air conditioners regardless of the manufacturer.
- Easy installation without drilling and without additional tools.
- The material is durable, UV-resistant, water-repellent and washable at 40°C.



Example 1

Example 2

