

Highlights



Motor

Bafang M500, 250
Watt
Torque: 95Nm



Battery

Samsung 20 Ah /
750 Wh
36V Li-Ion
removable



Frame

19" aluminium



Fork

Suntour
XCM 29"



Brakes

Hydraulic, discs
Brand: Shimano



Tyres

Reflective
Kenda, CST 29"
2.20



Gear shift

9 gears
Shimano Alivio



Weight

26,5 kg
Load capacity:
120 kg

•

Range

60-80 km

•

Support

up to 25 km/h in
3 steps

The Be Cool eMTB-Pro1 is a powerful mountain e-bike designed for adventure seekers!

Thanks to the powerful Bafang M500 motor with 250 watts and 95 Nm of power, you can conquer any terrain. The removable battery with 20 Ah and 720 Wh capacity and high-quality Samsung cells, gives you the freedom for long rides.

The hydraulic disc brake provides reliable braking power to keep you safe in any situation. With the 9-speed gears, you are always in control and can take on any challenge.

Experience carefree rides with the Be Cool eMTB-Pro1.



Oblique view right



Front view



Oblique view left



Side view left




Detail view battery

Specifications:

Frame

The range may vary depending on the terrain, weight of the rider, weather conditions, selected assistance level and other factors. The stated range is therefore only an estimate and is not to be understood as a binding value. Technical changes, errors and colour variations excepted.



9005151002249



Schuss Home Electronic GmbH,
Scheringgasse 3, 1140 Wien,
+43 (1) 970 21 - 0

Scope of delivery

- E-bike
- Charger
- Operating instructions

Warranty period

- 2 years

19" aluminium frame

Fork SUNTOUR, material: steel/aluminium

XCM suspension fork, hydraulic lockout, aluminium crown, stroke: 100mm

Steering head NECO, material: steel

Threadless, $\varnothing 28,6 \times 44 \text{ mm} \times 30 \text{ mm}$, H=19,9mm

Washer GINEYEA, Material: Aluminium

ID=1-1/8", H=10mm, 2PCS

Washer GINEYEA, material: aluminium

ID=1-1/8", H=5mm

Handlebar ZOOM, material: aluminium

MTB handlebar, 22.2mm \times 2.0T \times 720mm, H=20mm, grip width: 190mm, bore: 31.8mm

Stem ZOOM, material: aluminium

Stem, 28.6mm, Length=90mm, Matching bore 31.8mm, H=41mm, 7°

Grip, Material: Rubber/Aluminium

TPR R=22.2 \times 130mm

Handle, Material: Rubber/Aluminium

TPR L=22.2 \times 130mm

Chain KMC, material: steel

RO END, 1/2" \times 11/128" \times 128L, 9 speeds

Pedal FEIMIN, material: aluminium

Alloy pedal, 9/16", ball bearing, BS reflector

Front hub QUANDO, material: aluminium

Alloy hub, M9 \times 100mm \times 108mm 14G \times 36H, with quick release fastener

Rear hub QUANDO, material: aluminium

Alloy cassette, hub, M10 \times 135mm \times 145mm, 14G \times 36H, with quick release

Cassette SHIMANO, material: steel

9 gears, index, 11-36T, cassette

Front brake SHIMANO

MT200 hydraulic disc brake, M6 \times 20L, bolt, cable length 900mm

Brake disc, material: steel

160mm, 6-hole lock

Rear brake SHIMANO

MT200 Hydraulic disc brake, M6 \times 20L, bolt, cable length 1600mm


Brake disc, material: steel

160mm, 6-hole lock

Rim STAR, material: aluminium

29 \times 1.75, 14G \times 36H, H=20.5mm, A/V

The range may vary depending on the terrain, weight of the rider, weather conditions, selected assistance level and other factors. The stated range is therefore only an estimate and is not to be understood as a binding value.
Technical changes, errors and colour variations excepted.



9005151002249



Schuss Home Electronic GmbH,
Scheringgasse 3, 1140 Wien,
+43 (1) 970 21 - 0

Spokes, Material: Steel

14G*36H, F: 284/283mm, R: 285/283 mm

Tyres KENDA, Material: Rubber

29*2.20" KENDA logo

Inner tube KENDA, Material: Butyl

29*2.20, A/V48

Saddle VADER

Comfortable saddle

Seatpost ZOOM, material: aluminium

Aluminium seat post with quick release, 30.4*350mm

Quick-release GINEYEA, material: aluminium

35mm quick release

Front derailleur SHIMANO

Alivio shifting 9 gears

Cable shifting JAG

SP shift cable R: 1750

SHIMANO **sprocket**, material: aluminium/steel

Alivio 9 speeds rear derailleur

Battery PHYLION

36V, 20AH, Samsung cell 21700, EN15194-2017 standard

Motor BAFANG, material: aluminium

M500 36V*250W BAFANG motor, DS20, LCD-display, CL=49, 170L alloy crank

Charger PHYLION

GS/CE 36V, 3A charger, EU plug

Stand, material: aluminium

Aluminium rear stand adjustable

