

Construction heater 12000 Watt

with high voltage plug

Highlights

- Powerful 12000W for rapid heating of large rooms
- Robust stainless steel heating element for long service life
- Overheating protection for safe operation
- Sturdy full metal housing
 with insulated handle
- Splash-proof according to protection class IPX4

The construction heater 12000W offers a powerful and reliable heating solution for demanding areas of application.

With a heat output of 12000W and a voltage of 400V, the heater delivers heat quickly and evenly in large rooms - ideal for industrial environments. The durable stainless steel heating element ensures efficient heat distribution and a long service life.

Thanks to the thermostat control, the temperature can be adjusted as required, while the integrated overheating protection provides additional safety. The powerful fan ensures even air circulation and helps to keep the room temperature constant.



The sturdy metal housing is particularly resistant and ensures that the radiant heater works reliably even with intensive use. The insulated handle provides a secure grip and the freestanding, portable design makes the device flexible and easy to handle. The radiant heater also works without harmful exhaust fumes, unpleasant odours or moisture, making it particularly environmentally friendly.

With protection class IPX4, the construction radiant heater is also suitable for use in damp environments. The additional equipment with a relay and an automatic time delay function ensures precise control and increases safety. This radiant heater is therefore the ideal choice for workshops, construction sites and warehouses where a fast, efficient and safe heat source is required.







Oblique view left



Oblique view right





HOME ELECTRONIA



Construction heater 12000 Watt

with high voltage plug

Scope of delivery

- Construction radiant
- Operating instructions

Warranty period

2 years

Specifications:

Power: 12000W

• Voltage: 400V, 3~ 50Hz

• Heating element: stainless steel

• 1 fan stage: 52 Watt

• 2 heating levels: 6000W/12000W

• Adjustable thermostat control

Overheating protection

· Full metal housing

Insulated handle for more safety

· Freestanding and portable

• No exhaust fumes, no odours, no moisture

• Strong and durable construction

• IPX4 protection class

• With automatic time delay function

Dimensions:

• Product (W×H×D): 310×460×290 mm

Technical changes, errors and colour variations excepted.

Country of origin, unless otherwise stated: China

- Packaging (W×H×D): 320×490×300 mm
- Net/gross weight: 7.9 kg / 8.9 kg



