

Highlights

- **High-performance**
10 kW heating output for rapid heat
- **Propane-powered**
Efficient and portable (LPG)
- **High airflow**
500 m³/h, heats areas up to 100 m²
- **Safe**
Overheating protection and automatic shut-off in the event of gas leaks
- **Fully equipped**
Includes a pressure regulator and a 1.5 m gas hose for immediate use

Lieferumfang

- User manual
- Hose (1.5 m)
- Regulator

Garantiezeit

- 2 years

This portable gas heater, with a heat output of **10 kW**, runs on **propane (LPG)** and provides a fast and reliable source of heat in a variety of work and operational environments. Thanks to its compact design, the unit can be used flexibly, for example on building sites, in utility and agricultural buildings, greenhouses, or at sporting events.

A specially developed nozzle with an increased oxygen supply promotes **complete and efficient combustion** and helps to ensure even heat distribution. The heater has a **motor power of 27 W** and achieves an **air flow rate of 500 m³ per hour**, enabling it to heat areas of up to **100 m²**. **Gas consumption is 0.7 kg per hour**, ensuring economical operation.

To ensure safe use, the unit is fitted with **overheating protection** and an **automatic shut-off function to prevent gas leaks**. The integrated ignition function ensures simple and reliable start-up of the heater.

The scope of delivery includes a **pressure regulator** and a **1.5 m long gas hose**, so that the gas heater can be connected and put into operation straight away.



Specifications:

- Heat output: 10 kW
- Fuel type: Propane (LPG)
- Motor power: 27 W
- Fuel consumption: 0.7 kg/h
- Air flow: 500 m³/h
- Suitable heating area: up to 100 m²
- Operating pressure: 700 mbar
- Mains voltage: 220–240 V ~ 50 Hz
- Cable length: 1.2 m
- Protection rating: IPX4
- Overheating protection
- Gas cut-off (automatic shut-off in the event of gas leaks)
- Start-up/operation: Integrated ignition and deflation function for safe and easy operation
- Areas of use: Construction sites, agricultural and utility buildings, greenhouses, sporting events, etc.

Dimensions:

- Product (W×H×D): 180×290×335 mm
- Packaging (W×H×D): 385×305×220 mm
- Net/Gross weight: 2.8 kg / 4 kg