

Highlights

- **3 settings**
1 fan speed and 2 heating settings
- **Individually adjustable temperature**
from 10 to 49 °C
- **IPX2**
for use in the bathroom
- **Easy to use**
via touch control panel or remote control
- **Switchable swivel function**
for optimum heat distribution throughout the room
- **Window-open detection**
to prevent energy loss

Lieferumfang

- Bathroom fan heater
- User manual
- Wall-mounting kit
- Remote control

Garantiezeit

- 2 years

This stylish and powerful bathroom fan heater ensures pleasant warmth and a comfortable indoor climate at all times. Fitted with a PTC ceramic heating element, it provides particularly rapid and even heat distribution whilst maintaining high energy efficiency. With an output of 2000 watts, the unit brings your bathroom up to the desired temperature in no time at all; the temperature can be flexibly adjusted between 10 and 49 °C. Two heat settings offer additional customisation options to suit different needs. Thanks to the integrated timer with a weekly timer and a 12-hour timer, the fan heater can be individually programmed and optimally adapted to your daily routine – for cosy warmth exactly when you need it.

Operation is particularly convenient and can be carried out either directly via the built-in touch control panel or easily using the remote control. The switchable oscillation function distributes the warm air evenly throughout the room, ensuring a pleasant feeling of warmth at all times. The intelligent open-window detection system detects a rapid drop in temperature and automatically switches the appliance off to prevent energy loss.

With its modern design, the fan heater blends harmoniously into any bathroom and impresses with its successful combination of performance, comfort and efficiency.



Specifications:

- Mains voltage: 220–240 V ~ 50 Hz
- Max. power consumption: 2000 W
- 3 settings: 1 fan speed, 2 heat settings (1200 W / 2000 W)
- Adjustable thermostat: 10°C–49°C
- Weekly programme (weekly timer)
- 12-hour timer
- Open window detection
- On/off switch on the unit
- LED display
- Overheating protection
- Splash-proof to IPX2 standard
- Rapid and effective heat distribution
- Wall mounting
- with remote control

Dimensions:

- Product (W×H×D): 560×185×117 mm
- Packaging (W×H×D): 590×225×140 mm
- Net/Gross weight: 2.2 kg / 2.6 kg